



## CSGE 2885

### SMOKE DETECTOR / STROBE / BELL GUARD

#### DESCRIPTION

The CHASE SECURITY EXPANDED METAL ENCLOSURE has been designed to protect smoke detectors, strobes, bells, and other devices against vandalism or accidental damage. It is designed for Prisons, HUD Projects, Universities, Hotels, Parks, Schools, Hospitals, and other public locations where both functionality and aesthetics count.

Chase two-piece construction expanded metal enclosure is capped for safety and provides for ease of installation and maintenance of equipment once installed. For over 30 years Chase expanded metal products have been manufactured in a variety of sizes, styles and finishes, and sold to OEM accounts and distribution.



**Can be used in a variety of applications.**

#### FEATURES

- ◆ Constructed of quality 16-gauge expanded steel with a diamond pattern of 1" by 3/8" openings.
- ◆ Welded at all sides with reinforcement for a solid unit construction.
- ◆ Finish: white epoxy coating or stainless steel.
- ◆ Dimensions I.D. 7 1/2" x 7 1/2" x 5" deep.
- ◆ Easy to install.
- ◆ Unit can be provided with electrical provisions for conduit pipes of all sizes.
- ◆ Additional models available with 1" frames.
- ◆ Chase custom designs and builds to your specifications.

#### ACCESSORIES

- ◆ Matching custom service plates available for wall or conduit applications.

*Chase Security Systems, Inc., an MBE Enterprise, draws from over 30 years of experience selling to the Fire, Security, Computer, Sound, Food Processing, Forestry, Communications and Telecommunications industries. Many of our signature products are now being produced by other manufacturers but our expanded metal enclosures are still the product of choice for their strength.*

P.O. Box 30179, Chicago, IL 60630,  
Phone 773.775.7148, Fax 773.594.0078

[www.chasesec.com](http://www.chasesec.com)

© 2006 Chase Security Systems, Inc.



*Made with Pride in the U.S.A.*

Due to changes in industry, exact product dimensions and features may differ slightly from above.